

## Telecamere IP GAMS Sfera WiFi

| Codice | Modello | Descrizione |
|--------|---------|-------------|
|--------|---------|-------------|

|          |               |  |
|----------|---------------|--|
| TBI1000W | TWB212C22-I/L |  |
|----------|---------------|--|



Telecamera bullet IP **WiFi** Sfera a Led **2.0 Megapixel** Day & Night • **Onvif S/G/T** • range di frequenza 2.4GHz~2.4835GHz • standard Wireless IEEE802.11b/g/n • Ultra 265/H.265/H.264/MJPEG • Triplo Stream • **obiettivo fisso 2.8mm** • 0,02 lux a colori • **Smart IR** • Slot per Micro SD card • portata led 30m • porta Ethernet 10/100M Base-TX • 4 Privacy Zone • 2 ROI • audio • housing in alluminio e plastica IP67 • temperatura operativa -30°C~60°C • alimentazione 12Vcc/5.5W max.

|          |               |  |
|----------|---------------|--|
| TBI1010W | TWB212C24-I/L |  |
|----------|---------------|--|

Come modello TWB212C22-I/L, ma obiettivo 4.0mm

|          |               |  |
|----------|---------------|--|
| TDI1000W | TWD322C22-I/L |  |
|----------|---------------|--|



Minidome IP **WiFi** Sfera a Led **2.0 Megapixel** Day & Night • **Onvif S/G/T** • range di frequenza 2.4GHz~2.4835GHz • standard Wireless IEEE802.11b/g/n • Ultra 265/H.265/H.264/MJPEG • Triplo Stream • **obiettivo fisso 2.8mm** • 0,02 lux a colori • **Smart IR** • Slot per Micro SD card • portata led 30m • porta Ethernet 10/100M Base-TX • 4 Privacy Zone • 2 ROI • audio • housing in alluminio e plastica IP67 • temperatura operativa -30°C~60°C • alimentazione 12Vcc/5.5W max.